

自吸式泵浦
SELF - PRIMING PUMP

PRODUCT #
W09550
W09750



(3") W09550



(4") W09750

說明：

1. 同軸直接式構造，效能高，體積小，重量輕，不佔用空間，按裝方便。
(視需要亦可採聯軸式)
2. 採用鈎鋼機械軸封，抗磨損，不損軸心，免入棉紗之麻煩，延長抽水機壽命。
3. 本體特殊構造自吸能力高，揚水時間短。
4. 葉輪採開放式，污水雜物輸送力強。
5. 特殊副葉片之設計可消除軸向動力，動力損失比採平衡孔少。
6. 只要最初一次加水運轉，即可免除往後灌水的麻煩。
7. 材質可選購 FC, BC, SUS304, SUS316。

用途：

1. 產業工廠給水，排水用。
2. 建築工事給水，排水用。
3. 農耕栽培灌溉，排水用。
4. 下水道及淨水槽排水用。
5. 污水處理場排水用。
6. 化學工廠給水，排水用。

English:

1. Coaxial construction. Simple mounting, only small area of foundation needed. Small size and install easily. Use shaft-coupling type while on need.
2. To ensure no leakage, we adopt mechanical seal. It protects the shaft to extend further working period.
3. Self-priming design, fast rising water.
4. With semi-open impeller, small block won't intervene pump working.
5. Impeller blades are design specially to erase the thrust form the shaft.
6. Fill up water in the pump case at the first time operation and the water will be maintain inside the pump by next operation will not need to refilled water.
7. Optional material : FC, BC, SUS 304, SUS 316.

Usage :

1. Manufacturing industry for water supply and water discharge.
2. Building site water supply and industry used.
3. Agricultural irrigation water supply and discharge used.
4. Sewage water discharge used.
5. Sewage treatment water discharge used.
6. Chemical factory water supply and discharge used.

(泵浦類)
PUMP

