



污物泵浦 SEWAGE PUMP

PRODUCT #
W25040

特性：

1. 此泵浦水流經特殊設計可抽取污泥，污物各種污水，均能發揮最大功效。
2. 葉輪為堅固耐磨採用特殊材質並用鎢鋼切片設計，各種污廢水均可以輕易排送。

適用：

市場積水，牧場，豬舍排水，淨化槽，污水廠各種污物，污水排除，大樓地下室，工業廢水，食品廠廢水排除。

Features:

1. This pump current of water may extract the semisolid material , contamination each kind of sewage, can display the biggest effect .
2. The impeller for firm uses the special material quality wear-resisting and designs with the tungsten steel slice, each kind of dirty waste water may easily the delivery .

Usage:

The city water, the herd , hog house draining water, sewage factory each kind of contamination, the drainage disposal, the building basement, the industrial waste, Food factory waste water disposal.

規格 (Specification):

產品編號	馬力	相數	口徑	極數	揚程 / 水量 (標準)		揚程 / 水量 (最高)		電壓
PRODUCT #	OUTPUT (HP)	PHASE (Ø)	DISCHARGE (INCH)	POLE (N)	HEAD(M)/CAPACITY(GPM)(STANDARDS)		HEAD(M)/CAPACITY(GPM)(HIGH)		VOLTAGE (V)
W25000	1	1Ø	2"	2	9	53	12	105	220
W250030	1	3Ø	2"	2	10	74	15	105	220
W25005	2	1Ø	2"	2	10	95	17	132	220
W25010	2	1Ø	3"	2	13	120	18	172	220
W25015	2	3Ø	3"	2	13	120	18	172	220
W25020	3	3Ø	3"	2	14	165	20	235	220
W25025	3	1Ø	3"	2	14	175	20	250	220
W25030	5	3Ø	3"	2	18	203	25	290	220
W25040	7.5	3Ø	4"	2	21	240	30	343	220

產品名稱 (Product description)				產品編號 Product #	W25040
7.5HP 4" 3PH 2PL SUBMERSIBLE PUMP				型號 (Item #)	TF734
		口徑	極數	馬力 OUTPUT	7.5 (HP)
		DISCHARGE (INCH)	POLE		
		4"	2 (N)		
		相數	電壓		
		PHASE	VOLTAGE		
		3 (Ø)	220 (V)		
		揚程 / 水量 (標準)			
		HEAD(M)/CAPACITY(GPM)(STANDARDS)			
		21	240		
		揚程 / 水量 (最高)			
		HEAD(M)/CAPACITY(GPM)(HIGH)			
		30	343		



(泵浦類)
PUMP

