

EK 型軸流泵浦 SUBMERSIBLE PUMP

PRODUCT # W45040

特性:

- 1. 消費電力省 1/3, 適合長時間使用。
- 2. 大水量,大口徑,使用方便又省時。
- 2. 八小星、八口侄、庆田刀使入自时。 3. 特殊葉輪流速設計,性能佳,效率高,對輕量固體能發揮最大功效。 4. 馬達內裝有過載保護器,防止馬達燒毀。 5. 採用進口矽碳鋼 SIC 軸承,耐磨耗,耐久使用,完全防水。

- 6. 採用德國進口不鏽鋼軸承,可提供長時間運轉。

材質:

外型內筒採不鏽鋼板裝成,外上蓋上軸承座及導流盤採特殊鉋金鋼組。

用途:

養魚用進水,循環水,換水,景觀魚池,過沪排水,海水適用。

Features:

- Large flow pump design and save time for transfer and convenience.
 Large flow volume and large caliber to save time and more convenience.
 Special designed impeller, develops with best efficiency on light solid.
 Install Auto-Cut fixture to prevent motor burning out.

- 5. Install SIC seal to ensure wearing resistant, durability and water resistant out.
- 6. Install Germany bearing for long operation.

Material:

Motor Frame are made of stainless steel. Outer Upper cover, Diversion and Motor Bottom Cover are made of alloy copper.

Usage:

Water supply in fish farm, water circulation or other fishery. Landscape pond, draining water for a filter or seawater.

Product Description:

產品名稱 (Product description)		產品編號 Product #	W45040
1HP (1&3PH) 4" SUBMERSIBLE PUMP		型號 (Item #)	TL-114
極數	口徑	馬力OUTPUT	1 (HP)
POLE	DISCHARGE (INCH)		
2 (N)	4"		
電壓	相數		
VOLTAGE	PHASE		
220 (V)	1 (Ø)		
揚程/水量(標準) HEAD(M)/CAPACITY(GPM)(STANDARDS)		Friday and these	
揚程/水量(最高)			
HEAD(M)/CAPACITY(GPM)(HIGH)		Q	
3	211		
	極數 POLE 2 (N) 電壓 VOLTAGE 220 (V) 揚程/水 HEAD(M)/CAPACITY 1.5 揚程/水 HEAD(M)/CAPAC	極數 口徑 POLE DISCHARGE (INCH) 2 (N) 4" 電壓 相數 VOLTAGE PHASE 220 (V) 1 (Ø) 揚程 / 水量 (標準) HEAD(M)/CAPACITY(GPM)(STANDARDS) 1.5 185 揚程 / 水量 (最高) HEAD(M)/CAPACITY(GPM)(HIGH)	極數 口徑 馬力OUTPUT POLE DISCHARGE (INCH) 2 (N) 4" 電壓 相數 VOLTAGE PHASE 220 (V) 1 (Ø) 揚程/水量(標準) HEAD(M)/CAPACITY(GPM)(STANDARDS) 1.5 185 揚程/水量(最高) HEAD(M)/CAPACITY(GPM)(HIGH)

(泵浦類) **PUMP**

